

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1 and 10 in accordance with the following:

1. (CURRENTLY AMENDED) A paper ejecting mechanism, comprising:
an ejecting roller which ejects a paper printed on by a printhead in an ejecting direction;
and
a paper stand rotatably installed under the ejecting roller to rotate in a direction relative to the ejecting roller which such that the paper stand rotates to an upper limit thereof and supports the paper when the ejecting roller is rotated in an ejecting direction, and ~~which~~ rotates to a lower limit thereof and drops the paper into an output tray when the ejecting roller is rotated in a reverse direction to the ejecting direction.

2. (PREVIOUSLY PRESENTED) A paper ejecting mechanism comprising:
an ejecting roller which ejects a paper printed on by a printhead in an ejecting direction;
and
a paper stand installed under the ejecting roller which supports the paper when the ejecting roller is rotated in an ejecting direction, and drops the paper into an output tray when the ejecting roller is rotated in a reverse direction to the ejecting direction,
wherein the ejecting roller comprises:
a gear and
a shaft; and
the paper stand comprises:
a wing shaft parallel to the shaft of the ejecting roller,
a wing gear fixed to an outer circumference of the wing shaft and engaged with the gear of the ejecting roller,
a wing, an end of which is rotatably connected to the wing shaft and guides a path of the paper which is ejected, and
a friction clutch which transmits a rotation force of the wing gear to the wing.

3. (ORIGINAL) The paper ejecting mechanism of claim 2, wherein the paper stand further comprises:

a cylindrical member which is rotatably installed on the outer circumference of the wing shaft; and

a connection part which extends from the cylindrical member and is connected to the wing.

4. (ORIGINAL) The paper ejecting mechanism of claim 2, wherein the friction clutch comprises a clutch spring installed between the wing gear and a cylindrical member.

5. (ORIGINAL) The paper ejecting mechanism of claim 4, wherein the friction clutch further comprises a friction member fixed to the cylindrical member between the clutch spring and the cylindrical member.

6. (ORIGINAL) The paper ejecting mechanism of claim 3, wherein the wing is upwardly inclined at a predetermined angle with respect to the ejecting direction when supporting the paper.

7. (ORIGINAL) The paper ejecting mechanism of claim 6, wherein an end of the wing in the ejecting direction is higher than a flat surface formed by a contact side of the ejecting roller when supporting the paper.

8. (ORIGINAL) The paper ejecting mechanism of claim 3, wherein the wing protrudes downwardly in a direction perpendicular to the ejecting direction when the paper is dropped into the output tray.

9. (ORIGINAL) The paper ejecting mechanism of claim 2, wherein the wing further comprises:

a first stopper is installed at an upper limit of the wing and

a second stopper is installed at a lower limit of the wing;

the paper ejecting mechanism further comprising:

at least one relay gear disposed between the ejecting roller and a feed roller such that

when the feed roller is rotated in the ejecting direction the wing is upwardly rotated, and the rotation of the wing is stopped by the first stopper; and when the feed roller is rotated in a reverse direction to the ejecting direction the wing is downwardly rotated, and the rotation of the wing is stopped by the second stopper.

10. (CURRENTLY AMENDED) An ink-jet printer comprising:
a printing unit to print an image on a paper; and
a paper ejecting mechanism to support and eject the paper printed on by the printing unit, wherein the paper ejecting mechanism comprises:
an ejecting roller which ejects a paper printed on by a printhead in an ejecting direction;
and
a paper stand rotatably installed under the ejecting roller to rotate in a direction relative to the ejecting roller such that the paper stand ~~which~~ rotates to an upper limit thereof and supports the paper when the ejecting roller is rotated in an ejecting direction, and ~~which~~ rotates to a lower limit thereof and drops the paper into an output tray when the ejecting roller is rotated in a reverse direction to the ejecting direction.

11. (PREVIOUSLY PRESENTED) An ink-jet printer comprising:
a printing unit to print an image on a paper; and
a paper ejecting mechanism to support and eject the paper printed on by the printing unit, wherein the paper ejecting mechanism comprises:
an ejecting roller which ejects a paper printed on by a printhead in an ejecting direction;
and
a paper stand installed under the ejecting roller which supports the paper when the ejecting roller is rotated in an ejecting direction, and drops the paper into an output tray when the ejecting roller is rotated in a reverse direction to the ejecting direction,
wherein the ejecting roller comprises:
a gear and
a shaft; and
the paper stand comprises:
a wing shaft parallel to the shaft of the ejecting roller,
a wing gear fixed to an outer circumference of the wing shaft and engaged with the gear of the ejecting roller,
a wing, an end of which is rotatably connected to the wing shaft and

guides a path of the paper which is ejected, and
a friction clutch which transmits a rotation force of the wing gear to the wing.

12. (ORIGINAL) The ink-jet printer of claim 11, wherein the paper stand further comprises:
a cylindrical member which is rotatably installed on the outer circumference of the wing shaft; and
a connection part which extends from the cylindrical member and is connected to the wing.

13. (ORIGINAL) The ink-jet printer of claim 11, wherein the friction clutch comprises a clutch spring installed between the wing gear and the cylindrical member.

14. (ORIGINAL) The ink-jet printer of claim 13, wherein the friction clutch further comprises a friction member fixed to the cylindrical member between the clutch spring and the cylindrical member.

15. (ORIGINAL) The ink-jet printer of claim 12, wherein the wing is upwardly inclined at a predetermined angle with respect to the ejecting direction when supporting the paper.

16. (ORIGINAL) The ink-jet printer of claim 15, wherein an end of the wing in the ejecting direction is higher than a flat surface formed by a contact side of the ejecting roller when supporting the paper.

17. (ORIGINAL) The ink-jet printer of claim 12, wherein the wing protrudes downwardly in a direction perpendicular to the ejecting direction when the paper is dropped into the output tray.

18. (ORIGINAL) The ink-jet printer of claim 11, wherein the wing further comprises:
a first stopper installed at an upper limit of the wing and
a second stopper installed at a lower limit of the wing;
the ink-jet printer further comprising:

at least one relay gear is disposed between the ejecting roller and a feed roller such that when the feed roller is rotated in the ejecting direction the wing is upwardly rotated, and the rotation of the wing is stopped by a first stopper installed inside a printer; and when the feed roller is rotated in a reverse direction to the ejecting direction the wing is downwardly rotated, and the rotation of the wing is stopped by a second stopper installed inside the printer.

19. (PREVIOUSLY PRESENTED) The paper ejecting mechanism of claim 2, further comprising:

a star wheel or other roller or mechanism disposed on the ejecting roller to assist in ejecting the paper printed on by the printhead in the ejecting direction.

20. (PREVIOUSLY PRESENTED) The paper ejecting mechanism of claim 11, further comprising:

a star wheel or other roller or mechanism disposed on the ejecting roller to assist in ejecting the paper printed on by the printhead in the ejecting direction.